



- 材料有不锈钢、黄铜。
- 工作压力可达275psig(18.9bar)。
- 尺寸为1/8in至1/2in、3mm至12mm。
- 可用于连接PFA、尼龙、PU管等多种软管。

锁母接头

BC **8** - **01** - *****
 (1) (2) (3) (4)

- (1) 快拧接头型号
BZL表示为不旋转弯头型号
- (2) 插气管外径

代号	4	6	8	10	12
气管外径	Φ4	Φ6	Φ8	Φ10	Φ12

- (3) 螺纹型式及尺寸


55°锥管螺纹					
代号	01	02	03	04	06
气管外径	R1/8	R1/4	R3/8	R1/2	R3/4

55°直管螺纹					
代号	G01	G02	G03	G04	G06
气管外径	G1/8	G1/4	G3/8	G1/2	G3/4

公制螺纹标准表示方法表示，例：M5，M10X1

- (4) 表示快拧接头螺母
空白:滚花螺母 S:六角螺母

结构图



代号/Code 外径规格 O.D.	空白/Blank	A	B
4	4X2.5		
6	6X4		
8	8X6	8X5	
10	10X8	10X6.5	
12	12X10	12X8	12X9

BU 快拧直通



MODEL
BU04
BU06
BU08
BU10
BU12



BE 快拧正三通



MODEL
BE04
BE06
BE08
BE10
BE12



BV 快拧弯头



MODEL
IBV04
IBV06
IBV08
IBV10
IBV12



BC 快拧螺纹直通

MODEL	
BC04-M5	BC08-02
BC04-M6	BC08-03
BC04-01	BC10-02
BC04-02	BC10-03
BC06-01	BC10-04
BC06-02	BC12-02
BC06-03	BC12-03
BC08-01	BC12-04

BL 快拧L型螺纹弯头

MODEL	
BL04-M5	BL08-03
BL04-M6	BL10-02
BL04-01	BL10-03
BL06-01	BL10-04
BL06-02	BL12-02
BL08-01	BL12-03
BL08-02	BL12-04

BF 快拧内螺纹直通

MODEL	
BF04-01	BF10-02
BF06-01	BF10-03
BF06-02	BF10-04
BF08-01	BF12-02
BF08-02	BF12-03
BF08-03	BF12-04

BT 快拧螺纹正三通

MODEL	
BT04-M5	BT08-03
BT04-M6	BT10-02
BT04-01	BT10-03
BT06-01	BT10-04
BT06-02	BT12-02
BT08-01	BT12-03
BT08-02	BT12-04

北京尼克福斯阀门科技有限责任公司

地址:北京市大兴区丽园路港悦大厦7号楼1101
电话:86-010-66117795
传真:86-010-63733307 网址:www.nikfus.cn
邮编:100071 邮箱:sale1@nikfus.com

沧州尼克福斯仪表有限公司

地址:河北省沧州市南皮工业区
手机:13811443727 (微信同号)
邮编:061599 网址:www.nikfus.cn